

















## Equipment for mini and backhoe excavators

## INFORMATION 2

1					<p>There are two types of Pinlock Quick Hitches</p> <p><b>1) Standard PL Pinlock:</b></p> <ul style="list-style-type: none"> <li>- is attached to the bucket's std. mounting</li> <li>Advantages: Attached to existing bucket mounting</li> <li>Disadvantage: Extended pin to cutting edge dimension - reduces break-out force, not as strong as the Pinlock 99.</li> </ul> <p><b>2) Type 99 Pinlock (Hydrema type)</b></p> <ul style="list-style-type: none"> <li>- with reversible attachment</li> <li>Advantages: Similar to Safelock with a strong box shape. Hence the attachment can be used on other machine types. Visible locking marker.</li> <li>Disadvantage: Slightly increased pin to cutting edge dimension, when compared to Safelock.</li> </ul> <p><b>Safelock</b></p> <ul style="list-style-type: none"> <li>Advantages: Only QH worldwide to open and close mechanically without use of tools.</li> </ul> <p><b>Trilock</b></p> <ul style="list-style-type: none"> <li>- mechanic and hydraulic</li> <li>Advantages: Efficient and strong quick hitch.</li> </ul> <p>Trilock and Safelock have similar QH mounting+mech. release button. M2=SL10 M5=SL30 M8=SL40</p>
2					
3					
4					
	Trilock M2-M5 mounting plate	Safelock SL10-30 mount. plate	M8 - SL40 mounting plate	Powertilt hydr. swing 2 x 90°	